





12GP

(



- Gooseneck Heavy Duty Tandem Axle Pipe Trailer comes in 83" width and in lengths of 18' and 20' Approximate Carrying Capacity is 9,070# for the 18' and 8,900# for the 20'
 - 2-5/16" Ball Adjustable Pipe Coupler 16" Tires (8 bolt)
 - 8" Channel Neck 5" x 3" x 1/4" Angle Frame
 - 2-7/8" Pipe Square Back Top Rail w/Self Sealing Plugs
- Two 6,000# EZ Lube Axles w/Electric Brakes 4' Slide In Channel Ramps

14GP



- Gooseneck Heavy Duty Tandem Axle Pipe Trailer comes in 83" width and in lengths of 20' and 24' ■ Approximate Carrying Capacity is 10,800# for the 20' and 10,430# for the 24'
 - 2-5/16" Ball Adjustable Pipe Coupler 16" Tires (8 bolt) ■ 8" Channel Neck ■ 5" x 3" x 5/16" Angle Frame
- 3" Square Tubing Top Rail Two 7,000# EZ Lube Axles w/Electric Brakes ■ 4' Slide In Channel Ramps

14GN/1



- Tandem Axle Gooseneck Trailer comes in 102" width and in lengths ranging from 20'+5' to 30'+5' ■ Approximate Carrying Capacity ranges from 7,780# to 9,080#, depending on length of trailer
 - 2-5/16" Ball Adjustable Pipe Coupler on Gooseneck, 3" ID on Pintle
 - 16" Tires (8 bolt) 12" I-Beam Neck 12" I-Beam Frame
- 5" Channel Side Rail w/Rub Rail, Stake Pockets and Chain Spools
- Two 7,000# EZ Lube Axles w/Electric Brakes 5' Dovetail w/Double Hinged Spring Assist Fold Over Ramps

20GN/20PH



- Tandem Axle Gooseneck Trailer comes in 102" width and 20' + 5' length
 14,870# Approximate Carrying Capacity
 - 2-5/16" Ball Adjustable Pipe Coupler on Gooseneck, 3" ID on Pintle
 - 16" Tires (8 bolt) 12" I-Beam Neck 12" I-Beam Frame
 - 5" Channel Side Rail w/Rub Rail and Stake Pockets
 - Two 10,000# Dual Wheel Axles w/Electric Brakes
 - 5' Dovetail w/Double Hinged Fold Over Ramps

21GN



- Triple Axle Gooseneck Trailer comes in 102" width and in lengths of 20'+5' and 24' + 5' Approximate Carrying Capacity for the 20' + 5' is 15,920# and 15,450# for the 24' + 5' 2-5/16" Ball Adjustable Square Crank Type Coupler 16" Tires 12" I-Beam Neck 12" I-Beam Frame
 - 5" Channel Side Rail w/Rub Rail, Stake Pockets and Chain Spools
 Three 7,000# EZ Lube Axles w/Electric Brakes
 - 5' Dovetail w/Double Hinged Spring Assist Fold Over Ramps

22GN



- Tandem Dual Axle Gooseneck Trailer comes in 102" width and in lengths ranging from 20'+5' to 35'+5', 36' and 40'
- Approximate Carrying Capacity ranges from 14,400# to 16,820#, depending on length of trailer 2-5/16" Ball Adjustable Square Crank Type Coupler 16" Tires (8 bolt) 12" I-Beam Neck 12" I-Beam Frame
 - 6" Channel Side Rail w/Rub Rail, Stake Pockets and Chain Spools
 - Two General Duty 10,000# Dual Wheel Axles w/Electric Brakes (Oil Bath)
 - 5' Dovetail w/Double Hinged Spring Assist Fold Over Ramps

25GN



- Heavy Duty Tandem Dual Axle Gooseneck Trailer comes in 102" width and in lengths ranging from 20'+5' to 35'+5', 36' and 40'
- Approximate Carrying Capacity ranges from 17,460# to 19,410#, depending on length of trailer 2-5/16" Ball Square Crank Type Coupler
 - 16" Tires (8 bolt) 12" I-Beam Neck 12" I-Beam Frame
- 44K Adjustable Suspension 8" Channel Side Rail w/Rub Rail, Stake Pockets and Chain Spools Two Heavy Duty 10,000# Dual Wheel Axles w/Electric Brakes (Oil Bath) 5' Dovetail w/Double Hinged Spring Assist Fold Over Ramps

3XGN



- Super Duty Tandem Dual Axle Gooseneck Trailer comes in 102" width and in lengths ranging from 20'+5' to 30'+5' Approximate Carrying Capacity ranges from 21,370# to 23,770#, depending on length of trailer
- 30,000#, 2-5/16" Ball Adjustable Crank Type Coupler 17-1/2" Tires
- 12" I-Beam Neck 12 x 22# Frame up to 30' and 14 x 22# on 30' plus
- 44K Adjustable Suspension 8" Channel Side Rail w/Rub Rail, Stake Pockets and Chain Spools Two Heavy Duty 15,000# Dual Wheel Axles w/Electric Brakes (Oil Bath) 5' Dovetail w/Double Hinged Spring Assist Fold Over Ramps

SNOILAC



Deck on Neck



Center Pop-Up Dovetail



Underbody Toolbox



Sliding Winch

Trailers may be shown with options that are not standard. Carrying Capacities may vary with options. For a complete list of all trailer specifications and features, log on to www.bigtextrailers.com